

VertKleen Torque

All-In-One Heavy-Duty Vehicle Wash



VertKleen Torque is a one step heavy-duty all-in-one vehicle wash and wax. VertKleen Torque combines the finest cleaners, degreasers, brighteners and protectants with SynClean, our synthetic caustic replacement, and our patented SynTech acid replacement to offer the finest truck wash available. This one-step wash even contains Fusion, our patented anti-stick agent and natural waxes to protect the vehicle.

USE DIRECTIONS

Apply VertKleen Torque to any part of the vehicle to remove dirt, grease, and grime. Some brushing may be required. Rinse well with water to disperse wax and anti-stick coating. Torque may be applied by hand, bucket and brush, and/or foaming applicator systems.

DILUTION RATIO

New or Reconditioned Trucks - 20:1

Moderate Soil- 15:1

Heavy Soil- 10:1

Severe Soil- 5:1

HAZARD STATEMENT

May be harmful if swallowed.

Causes mild skin irritation.

Causes eye irritation.

SIGNAL WORD

Warning

PRECAUTIONARY STATEMENTS

Keep container tightly closed. Do not eat or drink while using this product. Wash hands thoroughly after handling. Avoid strong oxidizers. Dispose of in accordance with local, regional, federal or international regulations as specified.

OTHER

May cause mild skin irritation if not rinsed off with soap and water. May cause eye irritation if not rinsed out with copious amounts of water.



FIRST AID

If swallowed, drink two glasses of water. In case of eye contact, flush with water for two minutes. If symptoms persist seek medical advice

In case of skin contact wash thoroughly with soapy water. As with all chemicals, keep out of reach of children.

For Commercial and Industrial Use Only

GUARANTEE

MASEST guarantees this product to be free from defects and true to its contents. When used per label directions and dilutions, MASEST guarantees the use of this product will not void your manufacturers warranty for rust, corrosion and paint.



PO Box 236231, Cocoa, Florida 32923

813-451-7565 - sales@masest.co

Net Contents:

☐ 2.5 Gallons ☐ 55 Gallons ☐ 275 Gallons

